



R-22

Model		WTX09	WTX12	WTX18	WTX24	WTX30	WTX36	
Panel		NO.						
Alimentation unité extérieure		Ph-V-Hz	220-240/50	220-240/50	220-240/50	220-240/50	220-240/50	
Froid	Puissance	W	9000	12000	18000	24000	30000	36000
	Consommation	W	780	1120	1925	2080	3122/3000	3680
	Intensité	A	3,5	5,0	9,0	9,6	14.2/13.6	16,5
	EER	w/w	2,69	2,68	9,35	2,93	2.57/2.93	9,78
Chaud	Puissance	W	9500	12500	18500	24500	30500	36500
	Consommation	W	700	1100	1850	1650	3270/3190	4110
	Intensité	A	3,1	4,9	7,5	8,5	14.9/14.3	18,4
	COP	w/w	3,00	2,91	10,00	3,70	2.73/2.88	8,88
Consommation maximum		W	1000	1450	2500	2800	3450	5350
Intensité maximum absorbée		A	5,0	8,0	12,9	13,0	17,5	27,0
Compresseur	Model		PH130M1C-4DZDE2	PH200M1A-4DZ1	SHY33MC4-S	SHX33SC4-S	LH53VBDC	C-SBR145H15A
	Type		Rotary	Rotary	Rotary	Rotary	Rotary	scroll
	Marque		Toshiba	Toshiba	HIGHLY	Hitach	Mitsubishi	Sanyo
	Puissance	W	2230/2230	2880/2980	5200/5270	5710/5780	9400/9500±5%	11700/11700
	Input	W	725/755	960/995	1650/1690	1815/1880	2970/3080±5%	3750/3850
	Amp(LRA)	A	16,3	19	45	45	66/72	98
	Protection Thermique	A	4.15/3.9	5,00/4.50	7.6/7.2	8.35/8.00	13.7/13.6	17.4/17.3
	Capacité		External	External	Internal	Internal	Internal	External

		Huile Refrigérant	ml	25/370	35/370	50/400	60/400	60	60/440
				SUNISO-4GSD/NM56EP.350		SUNISO-4GSI,FREOL-K56J	FREOL-K56J or eq	DIAMOND/900	SAY56T OR EQUIVALENT .1700
Unité Intérieure	Moto-ventilateur	Model		YDK-14-4 (TB-SDJ-A07Bc)	YDK-14-4 (030020115)	YDK-27-4 A6 32020203R	YDK-27-4 A6	YDK-40-4A 1 320202014	YDK-40-4A 1 320202014
		Input	W	40	40	56	56	80	80
		Puissance	uF	1.2	1.2	1,8	1,8	2.5	2.5
		Vitesse	r/min	1350	1350	1300/1150/1000	1300/1150/1000	1280/1180/1080	1280/1180/1080
	Ventilateur unité	Diam x Longueur	mm	φ97χ583	φ97χ583	φ102×707	φ102×707	φ108×955	φ108×955
	Débit d'air		m3/h	400	600	900	900	1304/1250	1250
	Niveau sonore		dB(A)	29-36	31-42	42-46	42~46	43~49	43-49
	Dimensions L x h x l		mm	745×250×195	745×250×195	900*292*215	900*292*215	1235×325×250	1225*330*245
	Dimensions cartons		mm	833*330*278	833*330*278	983×377×300	1105×377×300	1445×410×320	1445×410×320
	Poids net		Kg	9/11	9/11	13/15	14/17.5	20/25	22/27
				ZX-G062	ZX-G062	ZX-G075	ZX-G055	ZX-G034	ZX-G034
Unité extérieure	Moto-ventilateur	Model		YDK-30-6E 2 (320222067)	YDK-35-6A H (320222005)	YDK-38-6B 320222014R	YDK-40-6A 1	YDK-60A-6F 320222018	YDK-200-6B 030020253
		Input	W	67	67	85	110	160	345
		Puissance	uF	2	2	2.5	3	4	10
		Vitesse	r/min	780±20	900	920	870	850	800±20
	Ventilateur unité extérieure	Diam x Longueur	mm	φ364×115	φ408×134	Φ408×134	Φ415	Φ460×180	φ556χ167
	Niveau sonore		dB(A)	49	54	54	54	56	58
	Dimensions L x h x l		mm	680*225*482	715×235×540	812×256×540	850×295×605	900×330×835	1000*350*990
	Dimensions cartons		mm	822×345×535	851×345×600	920×335×595	995×415×690	1030×440×960	1145×475×1120
	Poids net		Kg	24/28	28/33	38/42	42/49	65/80	98/106
				24/28	28/33	38/42	42/49	65/80	98/106
Refrigerant		g	530	R22/680g	R22/1230	R22/1200g	R22/2400	R22/3080g	
Pressions (haute/basse)		MPa	2.45/0.7	2.45/0.7	2.7/0.7	2.7/0.7	2.7/0.7	2.7/0.7	
Tube cuivre	Liquide/Gaz/longueur	mm	φ6.0+φ9.52×3500	φ6.0+φ9.52×3500	φ6.0+φ12.7×4000	φ9.52+φ15.88×5000	φ9.52+φ15.88×5000	φ9.52+φ19.05×5000	

Longueur maximale des	ml	15	15	15	15	15	15
--------------------------	----	----	----	----	----	----	----